

WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: (11) International Publication Number: WO 97/29057 A1 C03C 13/06 (43) International Publication Date: 14 August 1997 (14.08.97) PCT/EP97/00545 (21) International Application Number:

Published

With international search report.

(81) Designated States: AU, CA, CZ, HU, NO, PL, SI, SK, TR, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(22) International Filing Date: 6 February 1997 (06.02.97)

(30) Priority Data: DE 6 February 1996 (06.02.96) 196 04 238.0

(71) Applicant (for all designated States except US): ISOVER SAINT-GOBAIN [FR/FR]; Les Miroirs, 18, avenue d'Alsace, F-92400 Courbevoie (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): STEINKOPF, Bernd [DE/DE]; Marschnerstrasse 3, D-67061 Ludwigshafen (DE). HOLSTEIN, Wolfgang [DE/DE]; Herderstrasse 2, D-35315 Homberg (DE). KATZSCHMANN, Axel [DE/DE]; Helmholzstrasse 99, D-68723 Schwetzingen (DE). LOHE, Peter [DE/DE]; Ritterstrasse 5, D-67112 Mutterstadt (DE).

KUHNEN, WACKER & PARTNERS; Alois-Steinecker-Strasse 22, D-85354 Freising (DE).

(54) Title: MINERAL FIBER COMPOSITION

(57) Abstract

Mineral fiber composition which is decomposable in the physiological medium, characterised by the following constituents in weight percent: SiO₂ 30 to less than 51; Al₂O₃ higher than 11.5, in particular higher than 13, up to 25; CaO 2 to less than 23; MgO 0 to 15; Na₂O + K₂O higher than 10, up to 19; TiO₂ + Fe₂O₃ 6 to 18; various 0 to 3.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	u	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EB	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	Prance	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

Description

Mineral fiber composition

The present invention relates to a mineral fiber composition which is highly decomposable in the physiological medium.

The prior art describes several mineral fiber compositions which are specified to be decomposable in a physiological environment.

15

20

35

5

Physiological decomposition of mineral fiber compositions is of great significance inasmuch as various investigations point out that certain mineral fibers having very small diameters in the range of less than 3 μ m are suspected of being carcinogenic, whereas mineral fibers of such dimensions which are physiologically well decomposable do not show any carcinogenicity.

25 The mineral fiber compositions do, however, also have to have good processing properties with known methods for manufacturing small-diameter mineral wool, in particular the blast drawing method. This means particularly a sufficient processing range of e.g. 80°C 30 and suitable viscosity of the molten material.

In addition, the mechanical and thermal properties of the mineral fibers and of the respective products produced therefrom are of decisive importance. Mineral fibers are for instance utilised in a large scope for insulation purposes. Especially for utilisation in the industrial sector and for fire protection elements, the mineral fibers need to have sufficient heat stability.

It is the object of the invention to create a new mineral fiber composition which is distinguished by a high degree of physiological decomposability, shows good heat stability, has good processing properties, and can be produced economically.

10

15

The invention is based on the insight that this object may be achieved by specific mineral fiber compositions made up of silicon dioxide and alkaline earth oxides, and furthermore have a relatively high content of sodium oxide and/or potassium oxide and a substantial content of alumina as well as titanium oxide and/or iron oxide.

It was found that such mineral fiber compositions satisfy the combination of required properties, as there are a high degree of physiological decomposability, sufficient heat stability for insulation purposes in the industrial sector, and good processing properties in manufacturing the mineral wool proper and the products. This also includes the condition that the upper devitrification temperature of the molten material is preferably lower than 1,300°C. The mean fiber diameter is preferably 4 to 5 μm or less.

The subject matter of the invention is a mineral fiber composition which has a high degree of decomposability in the physiological medium and which is characterised by the following constituents in weight percent:

	\mathtt{SiO}_2	30 to less than 51
	Al ₂ O ₃	higher than 11.5; in particular
		higher than 13, up to 25
5	Ca0	2 to less than 23
	MgO	0 to 15
	$Na_2O + K_2O$	higher than 10 to 19
	$TiO_2 + Fe_2O_3$	6 to 18
	Various	0 to 3

10

What is referred to by Fe_2O_3 in this context are the contents of Fe_2O_3 and of FeO (expressed as Fe_2O_3).

In preferred embodiments of the invention, the Al_2O_3 content is around 14.2% (wt.), 14.5% (wt.) or 17.1% (wt.) as concentration values, or as minimum values of the concentration range up to 25% (wt.).

The concentration of Na₂O + K₂O preferably amounts to 10.4% (wt.) or 12% (wt.) as concentration values, or as minimum values of the concentration range up to 19% (wt.).

The mineral fiber compositions of the invention in particular can be well attenuated by the blast drawing method, which means that a mineral wool having good fineness and a low bead content is obtained.

Such mineral fibers attain high heat stability and 30 may also be used for fire protection structures having a resistance rating of at least 90 minutes which was determined in the so-called small-flame furnace according to DIN (German Industrial Standard) 4102, Part 17. Furthermore the limit temperatures of application as

determined according to AGQ 132 for the industrial sector are higher than 600°C.

Although the relatively high proportion of sodium oxide and/or potassium oxide results in a lowered melting point and thus in better processing properties in the melting and fiberising processes, the wool nevertheless surprisingly has a high heat stability.

For obtaining the above specified properties, it is advantageous that the contents of alkali oxides and alumina have a molar ratio of

 $(Na_2O + K_2O) : Al_2O_3 < 1:1,$

15

20

25

30

preferably a molar ratio of 1:1.

This molar ratio roughly corresponds to a weight proportion of alkali oxides and alumina of $\leq 0.7:1$.

The mineral fiber compositions according to the invention preferably may be melted in melting tubs fired by fossile fuels, in particular natural gas, at melting temperatures of 1,350 to 1,450°C. Such melting tubs are suited for obtaining a homogeneous molten material, which is a precondition for consistent product quality. Homogeneity of the molten glass material also facilitates reproduceability of the fiberisation process and thus of the thermal and mechanical product properties. Moreover the chemical composition of the mineral wool thus produced results in a consistently high degree of physiological decomposability.

In particular the addition of alumina, titanium oxide and iron oxide increases the heat stability of the mineral wool.

Preferably the mineral fiber compositions of the invention have the following constituents in weight per cent:

	\mathtt{SiO}_2	30 to less than 47
10	Al ₂ O ₃	higher than 11.5; in particular
		higher than 13, up to 24
	Ca0	4 to 20
	MgO	0 to 15
	$Na_2O + K_2O$	higher than 10, up to 18
15	$TiO_2 + Fe_2O_3$	7 to 16
	Various	0 to 2

In particular the mineral fiber compositions of the invention include the following constituents in weight per cent:

	SiO ₂	35 to 45
	Al_2O_3	higher than 12, up to 20
25	CaO	8 to 17.5
	MgO	2 to 10
	$Na_2O + K_2O$	higher than 10, up to 16
	$TiO_2 + Fe_2O_3$	7 to 15
	Various	0 to 2

30

The aluminum content of the composition is preferably between 13 and 20% (wt.).

5

10

The physiological decomposability of mineral fibers was determined in animal, i.e. in-vivo experiments by the so-called intratracheal test. Herefor the fibers to be tested were injected via the trachea into the bronchial system of the lungs of test animals (rats) by means of one or several injections. In rats as well as in human beings, particles which have penetrated into the lungs are decomposed physiologically by various defense mechanisms, e.g. macrophages, or chemical attack by lung fluid. At predetermined points of time, as a rule 35 animals are killed and the number of fibers, i.e. of non-decomposed fibers, inside the lungs is determined.

- This serves to determine how quickly the fibers are decomposed inside the lungs. Based on the development over time and by approved mathematical methods, one determines the half-life period of the fiber, i.e. the time period in which 50% of the fibers inside the lungs are decomposed. A lower half-life corresponds to a higher degree of physiological decomposability of the fiber. Thus the so-called Bayer B-01 fiber has a mean half-life of 32 days in the intratracheal test.
- In analogy with this B-01 mineral fiber, other mineral fibers were examined as well, which had half-life values in a range of less than 50 days and were rated to be non-carcinogenic.
- The physiological decomposability of the mineral fibers according to the invention even reached values which were clearly lower than 50 days, in particular a half-life of less than 40 days. These values rule out carcinogenicity.

The temperature behavior of the mineral fibers was determined in a small-flame furnace as specified by DIN 4102, Part 17, Determination of limit temperature of application.

The invention shall be described in more detail below by reference to exemplary embodiments.

10

Example 1

A mineral wool having the following composition in weight per cent was produced.

15

13		
	SiO ₂	41.3
	Al_2O_3	18.4
	CaO	15.0
	MgO	7.6
20	Na ₂ O	9.5
	K ₂ O	1.3
	\mathtt{TiO}_2	1.1
	Fe ₂ O ₃	5.6

- By using the blast drawing method and at an attenuating temperature between 1,300 and 1,400°C, this composition could readily be processed into mineral fibers having a mean diameter of 4,5 μm.
 - The wool met the conditions for the melting point test at 1,000°C.

Example 2

A mineral wool having the following composition in weight per cent was produced:

5		
	SiO ₂	39.3
	Al ₂ O ₃	18.3
	CaO	18.4
	MgO	6.6
10	Na ₂ O	4.5
	K ₂ O	6.2
	TiO ₂	0.4
	Fe_2O_3	6.1

By using the blast drawing method and at an attenuating temperature between 1,300 and 1,400°C, this composition could readily be processed into mineral fibers having a mean diameter of 4.5 to 5 μm .

20

25

Example 3

A mineral wool having the following composition in weight per cent was produced:

 SiO_2 44.0 Al_2O_3 18.5 CaO 13.0 MgO 5.2 30 Na_2O 6.6 K_2O 5.9 TiO_2 0.4 Fe_2O_3 6.2

By using the blast drawing method and at an attenuating temperature between 1,300 and 1,400°C, this composition could also readily be processed into mineral fibers having a mean diameter of 5.5 μm .

5

Example 4

A mineral wool having the following composition in 10 weight per cent was produced:

	\mathtt{SiO}_2	37.4
	Al_2O_3	22.2
	CaO	17.2
15	MgO	5.7
	Na ₂ O	4.5
•	K ₂ O	6.2
	TiO ₂	0.5
•	Fe_2O_3	6.1
20		

Example 5

A mineral wool having the following composition in 25 weight per cent was produced:

SiO ₂	43.9
Al ₂ O ₃	15.2
CaO	17.4
MgO	6.6
Na ₂ O	4.5
K ₂ O	6.2
\mathtt{TiO}_{2}	0.2
Fe_2O_3	6.0
	CaO MgO Na ₂ O K_2O TiO ₂

Example 6

A mineral wool having the following composition in weight per cent was produced:

	SiO_2	42.6
	Al_2O_3	17.9
	CaO	15.0
10	MgO	7.3
	Na ₂ O	4.4
	K ₂ O	6.1
	TiO ₂	0.4
	Fe_2O_3	6.3

Claims

5 1. Mineral fiber composition which is decomposable in the physiological medium, characterised by the following constituents in weight per cent:

30 to less than 51 SiO_2 10 higher than 11.5; in particular Al_2O_3 higher than 13, up to 25 CaO 2 to less than 23 MgO 0 to 15 $Na_2O + K_2O$ higher than 10 to 19 15 $TiO_2 + Fe_2O_3$ 6 to 18 Various 0 to 3

Mineral fiber composition according to claim 1,
 characterised by the following constituents in weight per cent:

30 to less than 47 SiO_2 Al_2O_3 higher than 11.5; in particular 25 higher than 13, up to 24 CaO 4 to 20 MgO 0 to 15 $Na_2O + K_2O$ higher than 10, up to 18 $TiO_2 + Fe_2O_3$ 7 to 16 30 Various 0 to 2




- 12 -

3. Mineral fiber composition according to claim 1 or 2, characterised by the following constituents in weight per cent:

 SiO_2 5 35 to 45 Al_2O_3 higher than 14, up to 20 CaO 8 to 17.5 MgO 2 to 10 $Na_2O + K_2O$ higher than 10, up to 16 10 $TiO_2 + Fe_2O_3$ 7 to 15 Various 0 to 2

INTERNATIONAL SEARCH REPORT



A. CLASSI IPC 6	IFICATION OF SUBJECT MATTER C03C13/06		
According t	to International Patent Classification (IPC) or to both national cla	estification and IPC	
	S SEARCHED		
Minimum d IPC 6	documentation searched (classification system followed by classifi CO3C	cation symbols)	
Documents	tion searched other than minimum documentation to the extent th	at such documents are included in the fields	searched
		·	
Electronic	data base consulted during the international search (name of data	base and, where practical, search terms used)	
C. DOCUM	MENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the	e relevant passages	Relevant to claim No.
P,X	WO 96 14274 A (ROCKWOOL INT ;JE LUND (DK); CHRISTENSEN VERMUND 17 May 1996 see page 4, line 7 - page 5, li see page 6, line 35 - page 8, l table	RUST (DK) ne 3	1-3
A	EP 0 583 791 A (SAINT GOBAIN IS February 1994 see page 10; table see page 17 - page 18; table	OVER) 23	1-3
A	EP 0 009 418 A (PARTEK AB) 2 Ap see page 4, line 33 - page 5, l examples		1-3
		-/	
į .		,	
	·		
X Furt	ther documents are listed in the continuation of box C.	X Patent family members are listed	in annex.
"A" docum consid "E" earlier filing "L" docum which citatio "O" docum	ent which may throw doubts on priority claim(s) or is cited to establish the publication date of another on or other special reason (as specified) went referring to an oral disclosure, use, exhibition or	"T" later document published after the int or priority date and not in conflict we cited to understand the principle or the invention "X" document of particular relevance; the cannot be considered novel or cannot involve an inventive step when the decay of the considered to involve an inventive step when the decay of the considered to involve an inventive considered to involve an indocument is combined with one or many considered to involve and indocument is combined with one or many considered to involve and indocument is combined with one or many considered to involve and indocument is combined with one or many considered to involve and indocument is combined with one or many considered to involve and indocument is combined with one or many considered to involve and indocument is combined with one or many considered to involve and indocument is combined with one or many considered to involve and indocument is combined with one or many considered to involve and i	ith the application but theory underlying the claimed invention to be considered to occurrent is taken alone claimed invention the theory are the theory are the theory of the theory of the the theory of the theor
P" docum later t	means ent published prior to the international filing date but han the priority date claimed	ments, such combination being obvior in the art. *&* document member of the same patent	
Date of the	actual completion of the international search	Date of mailing of the international se	earch report
2	4 April 1997	13.05.97	
Name and	mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fasc (+ 31-70) 340-3406	Authorized officer Van Bommel, L	

1

INTERNATIONAL SEARCH REPORT


Interest Application No PCT/EP 97/00545

		 7/00545
	tion) DOCUMENTS CONSIDERED TO BE RELEVANT	
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 83 01947 A (US ARMY) 9 June 1983 see page 1, last paragraph - page 2, paragraph 2; table I	1-3
A	PL 160 196 A (CENTRALNY OSRODEK BADAWCZO-ROZWOJOWY PRZEMYSLU IZOLACJI BUDOWLANEJ) 26 February 1993 see the whole document	1-3

1

INTERNATIONAL SEARCH REPORT

ormation on patent family members



Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9614274 A	17-05-96	AU 3871595 A AU 3871695 A BE 1009073 A DE 29515168 U WO 9614454 A FR 2726548 A NL 1001607 C NL 1001607 A	31-05-96 31-05-96 05-11-96 14-03-96 17-05-96 10-05-96 10-12-96 21-08-96
EP 0583791 A	23-02-94	CA 2121572 A WO 9404468 A AU 2433192 A BR 9206653 A CN 1087611 A FI 941816 A JP 7503696 T NO 941403 A NZ 248380 A SI 9300437 A SK 45594 A AU 668878 B HR 931148 A US 5554324 A	03-03-94 03-03-94 15-03-94 24-10-95 08-06-94 20-04-94 20-04-95 18-04-94 21-12-95 31-03-94 07-09-94 23-05-96 30-06-96 10-09-96
EP 0009418 A	02-04-80	JP 55047246 A	03-04-80
WO 8301947 A	09-06-83	EP 0095490 A	07-12-83
PL 160196 A		NONE	